



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Sika® Colma Cleaner

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Cleaning agent

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Österreich GmbH
Bingser Dorfstraße 23
6700 Bludenz
Telephone : +43 5 0610 0
E-mail address of person : EHS@at.sika.com
responsible for the SDS

1.4 Emergency telephone number

0043 1 4064343 (Giftinformationszentrale Wien)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

| | |
|--|---|
| Flammable liquids, Category 2 | H225: Highly flammable liquid and vapour. |
| Acute toxicity, Category 4 | H332: Harmful if inhaled. |
| Skin irritation, Category 2 | H315: Causes skin irritation. |
| Eye irritation, Category 2 | H319: Causes serious eye irritation. |
| Specific target organ toxicity - single exposure, Category 3, Central nervous system | H336: May cause drowsiness or dizziness. |
| Specific target organ toxicity - single exposure, Category 3, Respiratory system | H335: May cause respiratory irritation. |
| Specific target organ toxicity - repeated exposure, Category 2 | H373: May cause damage to organs through prolonged or repeated exposure if inhaled. |
| Aspiration hazard, Category 1 | H304: May be fatal if swallowed and enters airways. |
| Long-term (chronic) aquatic hazard, Category 3 | H412: Harmful to aquatic life with long lasting effects. |

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





| | | | | |
|--------------------------|-------------|--|--|--|
| Signal word | : | Danger | | |
| Hazard statements | : | H225 | Highly flammable liquid and vapour. | |
| | | H304 | May be fatal if swallowed and enters airways. | |
| | | H315 | Causes skin irritation. | |
| | | H319 | Causes serious eye irritation. | |
| | | H332 | Harmful if inhaled. | |
| | | H335 | May cause respiratory irritation. | |
| | | H336 | May cause drowsiness or dizziness. | |
| | | H373 | May cause damage to organs through prolonged or repeated exposure if inhaled. | |
| | | H412 | Harmful to aquatic life with long lasting effects. | |
| Precautionary statements | : | Prevention: | | |
| | | P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. | |
| | | P233 | Keep container tightly closed. | |
| | | P260 | Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. | |
| | | Response: | | |
| | | P301 + P310 | IF SWALLOWED: Immediately call a POISON CENTER/ doctor. | |
| | | P331 | Do NOT induce vomiting. | |
| | P370 + P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. | | |

Hazardous components which must be listed on the label:

xylene
propan-2-ol

Additional Labelling

The data sheet for medical personnel is available at the here provided emergency address.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

| Chemical name | CAS-No. EC-No. Registration number | Classification | Concentration (% w/w) |
|---|---|--|--------------------------|
| xylene Contains: ethylbenzene <= 25 % | 1330-20-7 215-535-7 01-2119488216-32-XXXX | Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 Aquatic Chronic 3; H412 | >=80 |
| propan-2-ol | 67-63-0 200-661-7 01-2119457558-25-XXXX | Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 | >= 20 - < 25 |

For explanation of abbreviations see section 16.

Components according to Detergents Regulation EC 648/2004

| Concentration | Components |
|---------------|-----------------------|
| 30 % and more | Aromatic hydrocarbons |

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Do not induce vomiting without medical advice.



Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.
Cough
Respiratory disorder
Excessive lachrymation
Erythema
Headache
Dermatitis
Loss of balance
Vertigo
See Section 11 for more detailed information on health effects and symptoms.
- Risks : Risk of serious damage to the lungs (by aspiration).
irritant effects
- May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
Harmful if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

- Unsuitable extinguishing media : Water

5.2 Special hazards arising from the substance or mixture

- Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

- Special protective equipment : In the event of fire, wear self-contained breathing apparatus.



for firefighters

Further information : Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Remove all sources of ignition.
Deny access to unprotected persons.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharge.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Follow standard hygiene measures when handling chemical products

Advice on protection against fire and explosion : Use explosion-proof equipment. Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Take precautionary



measures against electrostatic discharges.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in cool place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with local regulations.

Storage class (TRGS 510) : 3, Flammable liquids

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters * | Basis * |
|--|-----------|-------------------------------|------------------------------------|------------|
| xylene | 1330-20-7 | TWA | 50 ppm 221 mg/m ³ | 2000/39/EC |
| Further information: Identifies the possibility of significant uptake through the skin, Indicative | | | | |
| | | STEL | 100 ppm 442 mg/m ³ | 2000/39/EC |
| | | MAK-TMW | 50 ppm 221 mg/m ³ | AT OEL |
| | | MAK-KZW | 100 ppm 442 mg/m ³ | AT OEL |
| propan-2-ol | 67-63-0 | MAK-TMW | 200 ppm 500 mg/m ³ | AT OEL |
| | | MAK-KZW | 800 ppm 2.000 mg/m ³ | AT OEL |

*Values in the table refer to the latest EU-OEL and to the (Grenzwertverordnung GKV).

Biological occupational exposure limits

| Substance name | CAS-No. | Control parameters | Sampling time | Basis |
|----------------|-----------|---------------------------------------|--|---------|
| xylene | 1330-20-7 | Methylhippuric acid: 1,5 mg/l (Urine) | | VGÜ |
| | | methyl hippuric acid: 1,5 g/l (Urine) | At the end of a work week / at the end of a work day / at the end of a shift | VGÜ2014 |
| | | xylene: 1 mg/l (Blood) | End of workday | VGÜ2014 |



8.2 Exposure controls

Personal protective equipment

- Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water
- Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.
- Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (> 0,1 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.
- Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
organic vapor filter (Type A)
A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm
Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.
Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls

- General advice : Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : liquid
Colour : colourless
Odour : aromatic
Odour Threshold : No data available
- pH : Not applicable substance/mixture is non-soluble (in water)
- Melting point/range / Freezing : No data available



| | |
|--|--------------------------------------|
| point | |
| Boiling point/boiling range | : No data available |
| Flash point | : ca. 14 °C Method: closed cup |
| Evaporation rate | : No data available |
| Flammability (solid, gas) | : No data available |
| Upper explosion limit / Upper flammability limit | : 7 %(V) |
| Lower explosion limit / Lower flammability limit | : 1 %(V) |
| Vapour pressure | : 42,9963 hPa |
| Relative vapour density | : No data available |
| Density | : ca. 0,85 g/cm ³ (20 °C) |
| Solubility(ies) | |
| Water solubility | : No data available |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Auto-ignition temperature | : ca. 463 °C |
| Decomposition temperature | : No data available |
| Viscosity | |
| Viscosity, dynamic | : ca. 1 mPa.s (20 °C) |
| Viscosity, kinematic | : < 6,9 mm ² /s (40 °C) |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.



10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Components:

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 1.700 mg/kg

propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): < 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.



Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.

Aspiration toxicity

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

xylene:

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 2,2 mg/l
Exposure time: 73 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)



Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,17 mg/l
Exposure time: 7 d
Species: Daphnia (water flea)

propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 9.714 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Scenedesmus capricornutum (fresh water algae)): > 100 mg/l
Exposure time: 72 h

12.2 Persistence and degradability

This product does not contain any tensides according to the definition in the EU Detergents Regulation (EU/648/2004) (>0,2%).

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.



Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
- Austria - Waste catalogue : 55370
- Contaminated packaging : Completely emptied packagings can be given for recycling. Packaging containing remains of dangerous substances, as well as packagings disposed of remains can be unharmed eliminated in accordance with the regulations.
- 15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number

- ADR : UN 1993
IMDG : UN 1993
IATA : UN 1993

14.2 UN proper shipping name

- ADR : FLAMMABLE LIQUID, N.O.S.
(propan-2-ol, xylene)
IMDG : FLAMMABLE LIQUID, N.O.S.
(propan-2-ol, xylene)
IATA : Flammable liquid, n.o.s.
(propan-2-ol, xylene)

14.3 Transport hazard class(es)

- ADR : 3



IMDG : 3

IATA : 3

14.4 Packing group

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.



SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : None of the components are listed (= > 0.1 %).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH Information: All substances contained in our Products are
- registered by our upstream suppliers, and/or
- registered by us, and/or
- excluded from the regulation, and/or
- exempted from the registration.

Risk classification according to VbF : A I: Flash point less than 21 °C, at 15 °C not miscible in water
Specially dangerous flammable liquids

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

Water contaminating class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: 100 %

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 100 %

Productcode : M-VM04

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.



SECTION 16: Other information

Full text of H-Statements

| | | |
|------|---|---|
| H225 | : | Highly flammable liquid and vapour. |
| H226 | : | Flammable liquid and vapour. |
| H304 | : | May be fatal if swallowed and enters airways. |
| H312 | : | Harmful in contact with skin. |
| H315 | : | Causes skin irritation. |
| H319 | : | Causes serious eye irritation. |
| H332 | : | Harmful if inhaled. |
| H335 | : | May cause respiratory irritation. |
| H336 | : | May cause drowsiness or dizziness. |
| H373 | : | May cause damage to organs through prolonged or repeated exposure if inhaled. |
| H412 | : | Harmful to aquatic life with long lasting effects. |

Full text of other abbreviations

| | | |
|-------------------|---|--|
| Acute Tox. | : | Acute toxicity |
| Aquatic Chronic | : | Long-term (chronic) aquatic hazard |
| Asp. Tox. | : | Aspiration hazard |
| Eye Irrit. | : | Eye irritation |
| Flam. Liq. | : | Flammable liquids |
| Skin Irrit. | : | Skin irritation |
| STOT RE | : | Specific target organ toxicity - repeated exposure |
| STOT SE | : | Specific target organ toxicity - single exposure |
| 2000/39/EC | : | Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values |
| AT OEL | : | Austria. Limit values regulation - Annex I: Substance list |
| VGÜ | : | Austria. Biological limit values, VGÜ ASchG § 49 - |
| VGÜ2014 | : | Austria. Regulation on health surveillance in the workplace 2014 |
| 2000/39/EC / TWA | : | Limit Value - eight hours |
| 2000/39/EC / STEL | : | Short term exposure limit |
| AT OEL / MAK-TMW | : | Time Weighted Average |
| AT OEL / MAK-KZW | : | Short Term Exposure Limit |
| ADR | : | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| CAS | : | Chemical Abstracts Service |
| DNEL | : | Derived no-effect level |
| EC50 | : | Half maximal effective concentration |
| GHS | : | Globally Harmonized System |
| IATA | : | International Air Transport Association |
| IMDG | : | International Maritime Code for Dangerous Goods |
| LD50 | : | Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) |
| LC50 | : | Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period) |
| MARPOL | : | International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978 |
| OEL | : | Occupational Exposure Limit |



| | | |
|-------|---|--|
| PBT | : | Persistent, bioaccumulative and toxic |
| PNEC | : | Predicted no effect concentration |
| REACH | : | Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency |
| SVHC | : | Substances of Very High Concern |
| vPvB | : | Very persistent and very bioaccumulative |

Further information

Classification of the mixture:

| | |
|-------------------|------|
| Flam. Liq. 2 | H225 |
| Acute Tox. 4 | H332 |
| Skin Irrit. 2 | H315 |
| Eye Irrit. 2 | H319 |
| STOT SE 3 | H336 |
| STOT SE 3 | H335 |
| STOT RE 2 | H373 |
| Asp. Tox. 1 | H304 |
| Aquatic Chronic 3 | H412 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |
| Calculation method |

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

|| Changes as compared to previous version !

AT / EN