



EN13813:2002

13

1139

Leistungserklärung

gemäß Anhang III der Verordnung (EU) Nr. 305/2011 für das Produkt

Sika[®] Screed HardTop-80

Nr. 0203020400100000901029

1. Produkttyp: Eindeutiger Kenncode des Produkttyps:	Sika[®] Screed HardTop-80
2. Typen-, Chargen- oder Seriennummer oder ein anderes Kennzeichen zur Identifikation des Bauprodukts gemäß Artikel 11 Absatz 4:	Chargennummer: siehe Verpackung des Produktes
3. Verwendungszweck: Vom Hersteller vorgesehener Verwendungszweck oder vorgesehene Verwendungszwecke des Bauprodukts gemäß der anwendbaren harmonisierten technischen Spezifikation:	Zementöser Estrich / zementöse Beschichtung für die Innenanwendung in Gebäuden (Aufbauten gemäß technischem Merkblatt) EN 13813 CT – C80 – F8 – A9
4. Name, eingetragener Handelsname oder eingetragene Marke und Kontaktanschrift des Herstellers gemäß Artikel 11 Absatz 5:	Sika[®] Sika Österreich GmbH Bingser Dorfstrasse 23 6700 Bludenz Österreich
5. Kontaktanschrift: Gegebenenfalls Name und Kontaktanschrift des Bevollmächtigten, der mit den Aufgaben gemäß Artikel 12 Absatz 2 beauftragt ist:	nicht relevant (siehe Punkt 4)
6. System oder Systeme zur Bewertung und Überprüfung der Leistungsbeständigkeit des Bauprodukts gemäß Anhang V:	System 3 für das Brandverhalten System 4
7. Notifizierte Stelle (hEN): Im Falle der Leistungserklärung, die ein Bauprodukt betrifft, das von einer harmonisierten Norm erfasst wird:	Die notifizierte Stelle Nr. 1140 hat die Erstprüfung des Brandverhaltens nach System 3 vorgenommen und folgenden Prüfbericht ausgestellt: MA39-VFA2009-1114.02

Leistungserklärung



8. Notifizierte Stelle (ETA): Im Falle der Leistungserklärung, die ein Bauprodukt betrifft, für das eine Europäische Technische Bewertung ausgestellt worden ist:	nicht relevant
---	----------------

9. Erklärte Leistung


Wesentliche Merkmale	Leistung	Prüfnorm	Harmonisierte Technische Spezifikation
Brandverhalten	A1(fl)	EN 13501-1	EN 13813:2002
Freisetzung korrosiver Substanzen	CT	EN 13813	
Wasserdampfdurchlässigkeit	NPD	EN ISO 7783-2	
Druckfestigkeit	C80	EN 13892-2	
Biegezugfestigkeit	F8	EN 13892-2	
Verschleißwiderstand	A9	EN 13892-3	
Trittschallisolierung	NPD	EN ISO 140-1	
Schallabsorption	NPD	EN ISO 354	
Wärmedämmung	NPD	EN 12664	
Chemische Beständigkeit	NPD	EN 13529	



10. Erklärung

Die Leistung des Produkts gemäß den Nummern 1 und 2 entspricht der erklärten Leistung nach Punkt 9. Verantwortlich für die Erstellung dieser Leistungserklärung ist allein der Hersteller gemäß Punkt 4.

Unterzeichnet für den Hersteller und im Namen des Herstellers von:



Mähr Philipp (Produktingenieur)



Ing. Reto Monigatti (Geschäftsführer)

Bludenz, 20. März 2013

Ökologische, Gesundheits- und Sicherheitsinformationen (REACH)

Für detaillierte Angaben zur sicheren Handhabung, Lagerung und Entsorgung von chemischen Produkten, konsultieren sie bitte das aktuellste Sicherheitsdatenblatt unter www.sika.at, welches physikalische, ökologische, toxikologische und andere sicherheitsrelevante Daten enthält.

Rechtliche Hinweise:

Die vorstehenden Angaben, insbesondere die Vorschläge für Verarbeitung und Verwendung unserer Produkte, beruhen auf unseren Kenntnissen und Erfahrungen im Normalfall, vorausgesetzt die Produkte wurden sachgerecht gelagert und angewandt. Wegen der unterschiedlichen Materialien, Untergründen und abweichenden Arbeitsbedingungen kann eine Gewährleistung eines Arbeitsergebnisses oder eine Haftung, aus welchem Rechtsverhältnis auch immer, weder aus diesen Hinweisen, noch aus einer mündlichen Beratung begründet werden, es sei denn, dass uns insoweit Vorsatz oder grobe Fahrlässigkeit zur Last fällt. Hierbei hat der Anwender nachzuweisen, dass er schriftlich alle Kenntnisse, die zur sachgemäßen und erfolgversprechenden Beurteilung durch Sika erforderlich sind, Sika rechtzeitig und vollständig übermittelt wurden. Der Anwender hat die Produkte auf ihre Eignung für den vorgesehenen Anwendungszweck zu prüfen. Änderungen der Produktspezifikationen bleiben vorbehalten. Schutzrechte Dritter sind zu beachten. Im Übrigen gelten unsere jeweiligen Verkaufs- und Lieferbedingungen. Es gilt das jeweils neueste Produktdatenblatt, das von uns angefordert werden kann.



Für weitere Informationen:

Sika Österreich GmbH
Bingser Dorfstrasse 23
6700 Bludenz - Bings
Österreich

Phone +43 5 0610
Telefax +43 5 0610 1901
www.sika.at



EN13813:2002

13

1139

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011 for the product

Sika® Screed HardTop-80

Nr. 0203020400100000901029

1. Product Type: Unique identification code of the product-type:	Sika®Screed HardTop-80
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	Batch no.: see packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Cement based screed/coating for interior use in buildings (systems as per Product Data Sheet) EN 13813 CT – C80 – F8 – A9
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sika® Sika Österreich GmbH Bingser Dorfstrasse 23 6700 Bludenz Austria
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	not relevant (see 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 3 for Reaction to fire System 4
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	The notified body No.1140 performed the determination of reaction to fire class on the basis of type testing under system 3 and issued test report: MA39-VFA2009-1114.02
8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	not relevant (refer to item 7)

Declaration of Performance



9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	A1(fl)	EN 13501-1	EN 13813:2002
Release of corrosive substances (Cementitious Screed):	CT	EN 13813	
Water vapour permeability	NPD	EN ISO 7783-2	
Compressive strength	C80	EN 13892-2	
Flexural strength:	F8	EN 13892-2	
Abrasion Resistance:	A9	EN 13892-3	
Sound insulation:	NPD	EN ISO 140-1	
Sound absorption:	NPD	EN ISO 354	
Thermal resistance:	NPD	EN 12664	
Chemical resistance	NPD	EN 13529	

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Mahr Philipp (Product Engineer)



Ing. Fabio Monigatti (General Manager)

Bludenz, 20th March 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



For further information:

Sika Österreich GmbH
Bingser Dorfstrasse 23
6700 Bludenz - Bings
Österreich

Phone +43 5 0610
Telefax +43 5 0610 1901
www.sika.at