
SikaShield® E-KV-5K

DECLARATION OF PERFORMANCE

Nr. 57481096

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	57481096
2	INTENDED USE/S:	Bitumen damp proof course
3	MANUFACTURER:	Sika Österreich GmbH Dörrstraße 1 A-6020 Innsbruck Austria
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 14967:2006

Notified body/ies:

DECLARATION OF PERFORMANCE

SikaShield® E-KV-5K
57481096
01.09.2024, Version 1
1445

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Reaction to fire	E	System 3	EN 14967:2006
Watertightness, process B	passed	System 3	
Resistance to impact	≥ 2.000 mm	System 3	
Flexibility at low temperature (Pliability)	≤ -15 °C	System 3	
Durability			
- Watertightness after artificial ageing	passed	System 3	
- Chemical resistance	NPD		
Dangerous substances	no	System 3	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Raimund Ertl, Ing.
Head of Technical Service
Bitumen Sealing
Innsbruck, 01.09.2024



Nadine Sonderegger
Head of Research Development and
Quality Assurance
Innsbruck, 01.09.2024



End of information as required by Regulation (EU) No 305/2011

IN CONNECTION WITH THE DECLARATION(S) OF PERFORMANCE

Product name	Harmonised Standard	DoP Number
SikaShield® E-KV-5K	EN 13707	78717608
SikaShield® E-KV-5K	EN 13969	70133938
SikaShield® E-KV-5K	EN 13970	17545622

DECLARATION OF PERFORMANCE

SikaShield® E-KV-5K
57481096
01.09.2024, Version 1
1445



06

Sika Österreich GmbH, Innsbruck

DoP Nr. 57481096

EN 14967:2006

Bitumen damp proof course

SikaShield® E-KV-5K
Elastomeric bitumen-Membrane with polyester fleece inlay
Surface top/down: quartz sand/foil
1 m x 7,5 m x 5.0 mm

Reaction to fire	E
Watertightness, process B	passed
Resistance to impact	≥ 2.000 mm
Flexibility at low temperature (Pliability)	≤ -15 °C
Dangerous substances	no

<http://dop.sika.com>

DECLARATION OF PERFORMANCE

SikaShield® E-KV-5K
57481096
01.09.2024, Version 1
1445

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Österreich GmbH
Bingser Dorfstraße 23
A-6700 Bludenz
Phone: 05 0610 0
Fax: 05 0610 1901
www.sika.at

DECLARATION OF PERFORMANCE

SikaShield® E-KV-5K
57481096
01.09.2024, Version 1
1445