



EN 1504-3:2005

13

1139

Leistungserklärung

gemäß Anhang III der Verordnung (EU) Nr. 305/2011 für das Produkt

Sika[®] MonoTop[®]-211RFG

Nr. 0203020400100000681029

1. Produkttyp: Eindeutiger Kenncode des Produkttyps:	Sika[®] MonoTop[®]-211RFG
2. Typen-, Chargen- oder Seriennummer oder ein anderes Kennzeichen zur Identifikation des Bauprodukts gemäß Artikel 11 Absatz 4:	Chargennummer: siehe Verpackung des Produktes
3. Verwendungszweck: Vom Hersteller vorgesehener Verwendungszweck oder vorgesehene Verwendungszwecke des Bauprodukts gemäß der anwendbaren harmonisierten technischen Spezifikation:	Klasse R3 PCC Mörtel für die Betoninstandsetzung Prinzipien 3,4 und 7 – Methoden 3.1, 4.4, 7.1 und 7.2 nach EN 1504-9: 2008 Gemäß dem Anhang ZA Tabelle ZA.1
4. Name, eingetragener Handelsname oder eingetragene Marke und Kontaktanschrift des Herstellers gemäß Artikel 11 Absatz 5:	Sika[®] MonoTop[®] Sika Österreich GmbH Bingser Dorfstrasse 23 6700 Bludenz Österreich
5. Kontaktanschrift: Gegebenenfalls Name und Kontaktanschrift des Bevollmächtigten, der mit den Aufgaben gemäß Artikel 12 Absatz 2 beauftragt ist:	nicht relevant (siehe Punkt 4)
6. System oder Systeme zur Bewertung und Überprüfung der Leistungsbeständigkeit des Bauprodukts gemäß Anhang V:	System 2+ System 3 für das Brandverhalten
7. Notifizierte Stelle (hEN): Im Falle der Leistungserklärung, die ein Bauprodukt betrifft, das von einer harmonisierten Norm erfasst wird:	Die notifizierte Stelle Nr. 1139 , hat die Erstinspektion des Werkes und der werkseigenen Produktionskontrolle sowie die laufende Überwachung und Evaluierung der werkseigenen Produktionskontrolle nach dem System 2+ vorgenommen und Folgendes ausgestellt: Bescheinigung der Konformität der werkseigenen Produktionskontrolle 1234/08 . Die notifizierte Stelle Nr. 1140 hat die Erstprüfung des Brandverhaltens nach System 3 vorgenommen und folgenden Prüfbericht ausgestellt: MA39-VFA2009-1114.02

Leistungserklärung



8. Notifizierte Stelle (ETA): Im Falle der Leistungserklärung, die ein Bauprodukt betrifft, für das eine Europäische Technische Bewertung ausgestellt worden ist:	nicht relevant (siehe Punkt 7)
---	--------------------------------

9. Erklärte Leistung


Wesentliche Merkmale	Leistung	Prüfnorm	Harmonisierte Technische Spezifikation
Druckfestigkeit	≥ 25 MPa	EN 12190	EN 1504-3:2005
Chloridionengehalt	≤ 0,05 %	EN 1015-17	
Haftvermögen	≥ 1,5 MPa	EN 1542	
Karbonatisierungswiderstand	bestanden	EN 13295	
Elastizitätsmodul	≥ 15 MPa	EN 13412	
Temperaturwechselverträglichkeit	≥ 1,5 MPa	EN 13687-1	
Griffigkeit	NPD	EN 13036-4	
Wärmeausdehnungskoeffizient	NPD	EN 1770	
Kapillare Wasseraufnahme	≤ 0,5 kg.m ⁻² .h ^{-0.5}	EN 13057	
Brandverhalten	Klasse A1	EN 13501-1	
Gefährliche Substanzen	Siehe lokales Sicherheitsdatenblatt	-----	



10. Erklärung

Die Leistung des Produkts gemäß den Nummern 1 und 2 entspricht der erklärten Leistung nach Punkt 9. Verantwortlich für die Erstellung dieser Leistungserklärung ist allein der Hersteller gemäß Punkt 4.

Unterzeichnet für den Hersteller und im Namen des Herstellers von:



Mähr Philipp (Produktingenieur)



Samuel Plüss (Geschäftsführer)

Bludenz, 10.12.2014

Ökologische, Gesundheits- und Sicherheitsinformationen (REACH)

Für detaillierte Angaben zur sicheren Handhabung, Lagerung und Entsorgung von chemischen Produkten, konsultieren sie bitte das aktuellste Sicherheitsdatenblatt unter www.sika.at, welches physikalische, ökologische, toxikologische und andere sicherheitsrelevante Daten enthält.

Rechtliche Hinweise:

Die vorstehenden Angaben, insbesondere die Vorschläge für Verarbeitung und Verwendung unserer Produkte, beruhen auf unseren Kenntnissen und Erfahrungen im Normalfall, vorausgesetzt die Produkte wurden sachgerecht gelagert und angewandt. Wegen der unterschiedlichen Materialien, Untergründen und abweichenden Arbeitsbedingungen kann eine Gewährleistung eines Arbeitsergebnisses oder eine Haftung, aus welchem Rechtsverhältnis auch immer, weder aus diesen Hinweisen, noch aus einer mündlichen Beratung begründet werden, es sei denn, dass uns insoweit Vorsatz oder grobe Fahrlässigkeit zur Last fällt. Hierbei hat der Anwender nachzuweisen, dass er schriftlich alle Kenntnisse, die zur sachgemäßen und erfolgversprechenden Beurteilung durch Sika erforderlich sind, Sika rechtzeitig und vollständig übermittelt wurden. Der Anwender hat die Produkte auf ihre Eignung für den vorgesehenen Anwendungszweck zu prüfen. Änderungen der Produktspezifikationen bleiben vorbehalten. Schutzrechte Dritter sind zu beachten. Im Übrigen gelten unsere jeweiligen Verkaufs- und Lieferbedingungen. Es gilt das jeweils neueste Produktdatenblatt, das von uns angefordert werden kann.



Für weitere Informationen:

Sika Österreich GmbH
Bingser Dorfstrasse 23
6700 Bludenz - Bings

Phone +43 50 610
Telefax +41 58 610 1901



EN 1504-3:2005

13

1139

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011 for the product

Sika[®] MonoTop[®] -211RFG

Nr. 0203020400100000681029

Declaration of Performance

1. Product Type: Unique identification code of the product-type:	Sika[®] MonoTop[®] -211RFG
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	Batch no.: see packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Class R3 PCC mortar for the repair of concrete structures Principles 3,4 and 7 - methods 3.1, 4.4, 7.1 and 7.2 of EN 1504-9: 2008 Conforming to the Annex ZA Table ZA.1
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sika[®] MonoTop[®] Sika Österreich GmbH Bingser Dorfstrasse 23 6700 Bludenz Austria
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	not relevant (see 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 2+ System 3 for Reaction to fire
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	Notified factory production control certification body No. 1139 performed the initial inspection of the manufacturing plant and of factory production control under system 2+ and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 1234/08 . The notified body No.1140 performed the determination of reaction to fire class on the basis of type testing under system 3 and issued test report: MA39-VFA2009-1114.02



8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	not relevant (see 7)
--	----------------------

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Compressive strength	≥ 25 MPa	EN 12190	EN 1504-3:2005
Chloride Ion Content	≤ 0.05 %	EN 1015-17	
Adhesive Bond	≥ 1.5 MPa	EN 1542	
Carbonation Resistance	passed	EN 13295	
Elastic Modulus	≥ 15 MPa	EN 13412	
Thermal Compatibility freeze-thaw	≥ 1.5 MPa	EN 13687-1	
Skid resistance	NPD	EN 13036-4	
Coefficient of thermal expansion	NPD	EN 1770	
Capillary Absorption	≤ 0.5 kg.m ⁻² .h ^{-0.5}	EN 13057	
Reaction to fire	Class A1	EN 13501-1	
Dangerous substances	See local safety data sheet	-----	



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Mähr Philipp (Product Engineer)



Samuel Plüss (General Manager)

Bludenz, 10th Dec. 2014

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

